

VERITAS NETBACKUP™ 5240 APPLIANCE

A single-vendor, enterprise backup appliance
that is ready to backup in minutes

VERITAS

OVERVIEW

The Veritas NetBackup™ 5240 Appliance is a fully integrated Enterprise backup appliance with expandable storage and intelligent end-to-end deduplication for physical, virtual and cloud environments. Only Veritas appliances deduplicate on both the client and target side.

Veritas NetBackup™ 5240 Appliance delivers greater capacity, density and performance to reduce customers' operating and capital expenditures. As a purpose-built backup appliance (PBBA), it enables the ability to address customers' data center challenges while simplifying data protection needs.

PRODUCT HIGHLIGHTS

- **Suitable for any environment**—Starting at 4 TB and expandable up to 201 TB usable capacity, NetBackup 5240 is ideal for both remote offices and enterprise data centers.
- **Multiple functional roles**—Deploy as master server, media server, or both for a NetBackup domain.
- **NetBackup environments**—Easily expand or refresh existing NetBackup environments without disrupting operations.
- **Ultimate virtual machine protection**—Supports VMware® vSphere™ and Microsoft Hyper-V®, no proxy servers required.
- **Wide Area Network (WAN) optimization**—Up to 10x faster transfer rate for backups to cloud and replicating off-site.
- **NetBackup Accelerator**—Delivers traditional, full backups at the speed of incremental backups.
- **Simple and fast snapshot replication**—Accelerate snapshot replication management and granular file level recovery from any replicated snapshot image.
- **Operational simplicity**—Power up and walk through the installation wizard to start backing up in minutes.
- **Improve resource utilization**—Decrease backup storage up to 50 times and bandwidth consumption up to 99 percent.
- **Flexible deduplication options**—Deduplication at source or target; inline or post-process.
- **Dynamic storage**—Usable capacity can be any combination of up to 201 TB deduplication pool or Advanced Disk pool (non-deduplicated storage).
- **Eliminate Build-Your-Own Media Servers**—Reduce the operating cost, complexity, and frustrations of building and supporting your own media servers
- **Simple NetBackup software licensing**—Pay once for NetBackup software and freely replicate, change retention policies, and refresh hardware without penalties.
- **Auto Image Replication (AIR)**—Replicate backup images to a remote NetBackup domain for electronic vaulting and disaster recovery readiness.
- **Veritas™ Critical System Protection**—Protects against zero-day attacks and malicious insider threats.
- **Heterogeneous cloud gateway**—Serves as a gateway unit for sending backups to supported cloud storage vendors.
- **Resilient hardware architecture**—Multiple data paths deliver greater data protection and system availability, along with redundant hot swap components, featuring redundant power supplies, fan modules, and hot pluggable data disks.
- **Veritas AutoSupport**—The hardware monitoring feature ensures your backup environment is working at top efficiency, allowing you to anticipate needs before they become issues.
- **Veritas NetBackup™ Copilot for Oracle®**— A revolutionary new way to enable collaborative database backup and recovery.



NetBackup 5240 Appliance

TECHNICAL SPECIFICATION	NETBACKUP 5240	EXPANSION SHELF
Usable storage capacity (TB) ¹	4, 14, or 27	49 per shelf
Expansion shelves	NA	Up to 4 shelves
Minimum system usable capacity (TB) ²	4	NA
Maximum system usable capacity (TB) ²	27	196
Maximum appliance capacity max (TB) ²	201	
1 Gb Ethernet ports	up to 8	NA
10 Gb Ethernet ports	up to 8	NA
8 Gb Fibre Channel ports	up to 10	NA
Dimensions H x W x D (inches)	3.5 x 17.25 x 31.25	3.5 x 17.46 x 23.7
Maximum weight, with disk drives (lbs)	23.26 kg (51.28 lbs)	28 kg (62 lbs)
Typical power consumption (watts)	200	225
Maximum power consumption (watts)	550	580
AC voltage range (Volts)	100 - 127 200 - 240	100 - 127 200 - 240
AC frequency range (Hz)	50 to 60	50 to 60
Mean time to repair (hours)	< 1	< 1

PERFORMANCE

NetBackup 5240 delivers 53 TB/hour throughput.³

WARRANTY COVERAGE

One (1) year parts replacement and 90 days software.

MANAGEMENT

Through existing NetBackup Graphical User Interface.

PROTOCOL STANDARDS FOLLOWED

IPMI 2.0, SMBIOS 2.5, SAS 2.0a, ACPI rev 3, IP RFC0791

SAFETY AND EMC STANDARD COMPLIANCE

GB4943-2001, IEC 60950-1, UL 60950-1, FCC 47 CFR Part 15 Subpart A, EN 60950-1, EMC Directive 2004/108/EC, EN 55024: 1998+A1+A2, LVD Directive 2006/95/EC, ENERGY STAR compliant

MORE INFORMATION

Visit our website: <http://www.veritas.com>

ABOUT VERITAS TECHNOLOGIES LLC

Veritas Technologies LLC enables organizations to harness the power of their information, with solutions designed to serve the world's largest and most complex heterogeneous environments. Veritas works with 86 percent of Fortune 500 companies today, improving data availability and revealing insights to drive competitive advantage.

¹ Capacity is based on Base2, 1TB = 1,099,511,627,776 Bytes.

² Capacity values are calculated using Base2 (i.e. 1 TB = 1,099,511,627,776 bytes).

³ Observed performance is based on peak throughput using 48 clients with 4 streams per client at 98 percent client deduplication.

Veritas Technologies LLC
500 East Middlefield Road
Mountain View, CA 94043 USA
+1 (650) 527 8000
1 (866) 837 4827
veritas.com

For specific country offices and contact numbers, please visit our website.
<https://www.veritas.com/about/contact.html>

VERITAS™

V0237-2 7/16